

## DATA SHEET

### Water polishing system **Connect LT**

Parameters	Connect LT	Connect LT Bio
Catalogue No.	CB-1801	CB-1803
Grade 1 water resistivity at 25 °C	18.2 MΩ x cm	18.2 MΩ x cm
Grade 1 water conductivity at 25 °C	0.055 μS/cm	0.055 μS/cm
TOC	<5 ppb*	<5 ppb*
RNase	-	<0.01 ng/mL
DNase	-	<4 pg/μL
Bacteria	<0.01 CFU/mL	<0.01 CFU/mL
Endotoxins	<0.15 EU/mL	<0.001 EU/mL
Particles >0.22 μm	<1/ mL	<0.05/ mL
Dispense rate, ultrapure water	1.5–2.0 L/min	1.5–2.0 L/min
Display	7" touchscreen	7" touchscreen
Dispenser	Dispense port	Dispense port
TOC monitor	+	+
Temperature range	15–30 °C	15–30 °C
Relative humidity	20–80%	20–80%
Mains voltage	200–240 VAC	200–240 VAC
Power	130 W	130 W
Fuse	230 V, 3.15 A	230 V, 3.15 A
Width*Depth*Height	29x44x65 cm	29x44x65 cm
System weight	17 kg	17 kg
Operating weight	20 kg	20 kg
Tank	Not required	

\*In appropriate operating conditions <2 ppb, otherwise normally <5 ppb

#### Feedwater properties

Type of feedwater	Pre-treated
Feedwater conductivity	<100 μS/cm
TOC	<50 ppb
Feedwater pressure	0.4–4.0 bar
Temperature	5–35°C
pH	4–10
Iron	<0.1 ppm as CaCO <sub>3</sub>
Aluminium	<0.05 ppm as CaCO <sub>3</sub>
Manganese	<0.05 ppm as CaCO <sub>3</sub>
CO <sub>2</sub>	<30 ppm
Fouling Index	<5
Total chlorine	<1 ppm
Langelier Saturation Index	<+0.2